



INSTALLATION TIPS

LAZER STAR HID UPGRADE

These instructions are generalized instructions, your installation procedure will likely vary.

These HID Upgrades are for off-road use only and should never be used on a street licensed vehicle.

1. Begin by disconnecting the negative (-) terminal from the battery.
2. Locate your stock lamps and remove them by opening the front hood or access the factory bulbs from inside the fender wells. This procedure will vary widely from vehicle to vehicle.
3. Install the HID lamp into the headlight assembly in the reverse order you removed the stock lamp. Do not touch the lamp!
4. Using the screws provided mount the ballast in a location that won't interfere with the closure of the hood, where they will be safe and out of the way of moving parts and not near the radiator. Make sure the ballast is close enough to the lamp not too short that you cannot open the hood.
5. Depending on the vehicle there will be an oval sealed connector that was either connected directly to the stock lamp or to a short pig-tail wire that is connected to the lamp. Attempt to plug the oval male sealed plug into the RED colored female plug on the ballast. If it goes easily you may use this method to power the ballast. If it does not then you must use the pig-tail extension wire included by inserting the pins on the pig-tail into the stock plug or cut and splice.
6. Connect the HID lamp to the ballast. 2 round sealed plugs for each lamp. Match wire colors.
7. Please make sure all wires are zip tied tightly, and nothing is exposed or left hanging down.
8. Reconnect battery and test.

If you have any questions or comments please feel free to give us a call at 800.624.6234
Or you can fax us at 805.226.8150

**THANK YOU FOR CHOOSING
Lazer Star Lights!**

2734 Danley Court, Paso Robles, CA 93446
800-624-6234 • 805-226-8200 • f. 805-226-8150
info@lazerstarlights.com • lazerstarlights.com