



# ***INSTALLATION TIPS***

## ***MICRO B LENS REPLACEMENT***

**\*\*CAUTION: DO NOT TOUCH THE BULB OR INNER REFLECTOR.**

Doing so may cause damage to the lamp.

1. Slowly unscrew the lens cap in a counter-clockwise direction while at the same time holding the lens down (if yours is still there). This keeps the lens/lamp from twisting in the housing. Be careful not to drop the lens once the cap is removed.
2. Remove the lens, and lens O-ring(s).
3. Place the new O-ring in the groove of the cap, if it will not seat then stretch it a little, by taking it out and lightly tugging on it.
4. Place the new lens over the O-ring. Hold it by the edges so as not to get your fingerprints on the inside.
5. Grasp the light body, then screw the lens cover on 1/2 turn. Seat the lamp by pushing the lens all the way down and hold it down. Continue to screw on the lens cover while holding the lens down, until tight. When all is correct the mounting ring and the lens should not move.
6. You may want to use some "super glue" and reseal the wire grommet to insure water tightness. Remove any old sealer before applying.

Note: Weekend Concepts cannot be responsible for lamp or seal damage that may occur during reassembly; this includes any subsequent leaking or failure of any component.

If you have any questions or comments please feel free to give us a call at 800.624.6234  
Or you can fax us at 805.226.8150

**THANK YOU FOR CHOOSING  
Lazer Star Lights!**

2734 Danley Court, Paso Robles, CA 93446  
800-624-6234 • 805-226-8200 • f. 805-226-8150  
info@lazerstarlights.com • lazerstarlights.com