



Lazer Star Lights • 2734 Danley Court, Paso Robles, CA • 805.226.8200 • lazerstarlights.com

Part # 77132005 PreRunner LED Chase Tail

GENERAL NOTES:

* These instructions are also available on our website: lazerstarlights.com. Please check our website before you begin installation for any updated instructions as well as additional photos for your reference.

PARTS LIST:

- * (1) 77132005 (20" Single Row Multi-Function Light Bar)
- * (2) Bottom Mounts
- * (2) Side Mounts

Parts / Tools Needed to complete installation:

- * 13mm Wrench
- * 3mm Allen Wrench
- * 5mm Allen Wrench

APPROXIMATE INSTALL TIME: 1 HR

INSTALLATION:

1. This light has 5 different functions:

Red High, Red Low, Amber Left, Amber Right, and White

Depending on your application you can wire each of these functions separately or have them work together.



- 2. Black Wire = Ground
- Blue Wire = Left Amber
- Grey Wire = Right Amber
- Red Wire = White
- Yellow Wire = Red Low
- Green Wire = Red High



- 3. If you have pre-existing run, brake, turn, or reverse functions wired into your vehicle you can simply “tap” the corresponding wires into those functions. If you choose to “tap” into pre-existing wiring, no additional switches or fuses should be needed.
- 4. If you do not have preexisting wiring, you can wire each segment to a switch individually or in any combination you would like. An in-line 5 amp fuse is recommended for each function when wiring the segments this way.

Use and Care Tips:

- * Keep all wires away from hot or moving parts.
- * Always disconnect the battery when working with wiring.

Installation is Complete